

DRAIN LINE WITH NEUTRALIZER PIPED TO FLOOR DRAIN NOT SHOWN. DUPLICATE REQUIRED PIPING FOR HEATER(S) AND STORAGE TANK(S).
7. IF PERMITTED BY LOCAL CODES, A CHECK VALVE MAY BE USED IN PLACE OF A BACKFLOW PREVENTER.
8. REFER TO INSTALLATION CHAPTER OF OMM-0175 FOR AIR, GAS, AND CONDENSATE CONNECTIONS.
9. ALL (*) COMPONENTS ARE OPTIONAL FOR INSTALLATION UNLESS OTHERWISE STATED PER LOCAL CODE REQUIREMENTS.
10. THE FOLLOWING COMPONENTS SHALL BE FIELD SOURCED: CHECK VALVES, STRAINERS, BALL VALVES, BALANCING VALVES, PUMPS, TEMPERATURE SENSORS,
EXPANSION TANK, BACKFLOW PREVENTER.
11. DUIL DING DECIDE DUMP DETERMINED BY DULIMPING ENCINEED AND MINIMUM ELOW/VADIES BY DIGITEMP MODEL

11. BUILDING RECIRC PUMP DETERMINED BY PLUMBING ENGINEER AND MINIMUM FLOW VARIES BY DIGITEMP MODEL.

12. SEE CLEARANCE DIAGRAMS FOR APPROXIMATE INSTALLED FOOTPRINT WIDTH AND DEPTH.

PERCO Blauvelt, NY 10913				
INNOVATION – SINGLE UNIT, ONE STRAT STORAGE TANK, DIGITEMP JR				
DRWN BY.	DATE	DWG. NO:	REV.	
<u>AD</u>	032025	SD-A-1362 Page 1 of 1	Α	